

1. Features


1. Low loss realized with low DCR.
2. High performance realized by metal dust core.
3. Ultra low buzz noise, due to composite construction.
4. 100% Lead(Pb)-Free & Halogen-Free and RoHS compliant.



2. Applications

Commercial applications.


3. Dimensions



A	B	C	D	E
7.00Max	6.70Max	11.00Max	3.7±0.3	2.00±0.3

Unit:mm

Recommend PC Board Pattern



L	G	H
6.90	2.30	4.20

Note: 1. PCB layout is referred to standard IPC-7351B
 2. The above PCB layout reference only.
 3. Recommend solder paste thickness at 0.15mm and above.

4. Part Numbering

SEPI	706711	LN	-	R10	L	-	R1610
A	B	C		D	E		F

A: Series
 B: Dimension BxC
 C: Type Standard
 D: Inductance R10=0.10uH
 E: Inductance Tolerance L=±15%,M=±20%,N=±25%,Y=±30%
 F: Code DC Resistance, Marking direction cannot decide polarity.

5. Specification

Part Number	Inductance L0A DC (uh)	I rms (A)	I sat (A)Typ			DCR (mΩ)	Marking
		Typ	25℃	75℃	100℃		
SEPI706711LN-70NL-R1610	0.07±15%	76	134	124	114	0.16±10%	70N
SEPI706711LN-R10L-R1610	0.10±15%	76	93	86	79	0.16±10%	R10
SEPI706711LN-R12L-R1610	0.12±15%	76	76	69	65	0.16±10%	R12

Note:

1. Test frequency : Ls : 100KHz /1.0V.
2. Testing Instrument(or equ) : Agilent 4284A,E4991A,4339B,KEYSIGHT E4980A/AL,chroma3302,3250,16502.
3. Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40℃
4. Saturation Current (Isat) will cause L0 to drop approximately 30%.
5. The part temperature (ambient + temp rise) should not exceed 125℃ under worst case operating conditions.Circuit design,component,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
6. I rms Testing : Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components.
Therefore temperature rise should be verified in application conditions.
7. Rated DC current: The lower value of I rms and Isat.